


Features & Applications

The PDX-5 Mini DL Basic uses High Brightness **CREE LED** as its light source. It is housed in a new modern fixture for easy installation & application. It comes complete with a Constant Current Driver to ensure consistent brightness and optimal performance. The LED light provides high CRI lighting effect with negligible heat, UV or IR emission. They are ideal for pictures, antiques, jewelries, cosmetics etc. They can be easily applied in showcases, cabinets or under counters.

Dimensions



All Dimensions in mm




Product Specifications

Light Source	1 W High Power CREE LED
Driver Type	External Constant Current Driver
Driver Power Input	100~240vac, 50~60 Hz
Power consumption	Max 1.2W per lamp
Driver Output	350mA
Lumen per Lamp	Min 80 lm (Day Light)
Intensity per Lamp @ 1m	440 lux (Day Light) on 30 deg Lens
Lens Options	Standard: 30 deg. Custom: 60 deg
Colour Options	Standard: Day Light (Typ 6000K), Warm White (Typ 3000K) Custom: Red, Green, Blue, Amber
Operating Temperature	-5 ~+40 deg C
Estimated Lamp Life	50,000 hrs

Models

PDX-51YZZ



ZZ	Digits depict lens angle (deg)	30, 60. Standard: 30
Y	Digit depicts number of lamps per set	Standard: 3
X	Alphabet depicts LED colour	B: Day Light, E: Warm White, R: Red, G: Green, L: Blue, Y: Amber
Standard Models: PDB-51330, PDE-51330. MOQ applies for other models		

Prime Light Pte Ltd reserves the right to change the specification without prior notification.